

SYF-8813 Directonal LEDs Meets SAE J595 Class 2; Certified E6		
Flash Pattern	: Twelve selectable "strobing" patterns	1W x 3 LEDs
Working Voltage	: DC 12V~24V	Av. Current: 0.15A (12V)
Size	: 3.86"(98mm)Lx1.61"(41mm)Wx1.14"(29mm)H	
SYF-8814 Directonal LEDs Meets SAE J595 Class 1; Certified E6		
Flash Pattern	: Nineteen selectable "strobing" patterns	1W x 4 LEDs
Working Voltage	: DC 12V~24V	Av. Current: 0.35A (12V)
Size	: 4.65"(118mm)Lx1.61"(41mm)Wx1.14"(29mm)H	
SYF-8823 Directonal LEDs Meets SAE J595 Class 1; Certified E6		
Flash Pattern	: Twelve selectable "strobing" patterns	1W x 6 LEDs
Working Voltage	: DC 12V~24V	Av. Current: 0.35A (12V)
Size	: 3.86"(98mm)Lx2.76"(70mm)Wx1.14"(29mm)H	
SYF-8824 Directonal LEDs Meets SAE J595 Class 1; Certified E6		
Flash Pattern	: Nineteen selectable "strobing" patterns	1W x 8 LEDs
Working Voltage	: DC 12V~24V	Av. Current: 0.6A (12V)
Size	: 4.65"(118mm)Lx2.76"(70mm)Wx1.14"(29mm)H	
SYF-8813-3 Directonal LEDs Meets SAE J595 Class 1; Certified E6; ECE-R65 XA1 000045; XB1 000064; XR1 000065		
Flash Pattern	: Twelve selectable "strobing" patterns	3W x 3 LEDs
Working Voltage	: DC 12V~24V	Average Current: 0.35A (12V)
Size	: 3.86"(98mm)Lx1.61"(41mm)Wx1.14"(29mm)H	
SYF-8814-3 Directonal LEDs Meets SAE J595 Class 1; Certified E6; ECE-R65 XA1 000049; XB1 000058; XR1 000059		
Flash Pattern	: Nineteen selectable "strobing" patterns	3W x 4 LEDs
Working Voltage	: DC 12V~24V	Average Current: 0.7A (12V)
Size	: 4.65"(118mm)Lx1.61"(41mm)Wx1.14"(29mm)H	
SYF-8823-3 Directonal LEDs Meets SAE J595 Class 1; Certified E6; Meets ECE-R65 Class 2		
Flash Pattern	: Twelve selectable "strobing" patterns	3W x 6 LEDs
Working Voltage	: DC 12V~24V	Average Current: 0.7A (12V)
Size	: 3.86"(98mm)Lx2.76"(70mm)Wx1.14"(29mm)H	
SYF-8824-3 Directonal LEDs Meets SAE J595 Class 1 ; Certified E6; Meets ECE-R65 Class 2		
Flash Pattern	: Nineteen selectable "strobing" patterns	3W x 8 LEDs
Working Voltage	: DC 12V~24V	Average Current: 1.4A (12V)
Size	: 4.65"(118mm)Lx2.76"(70mm)Wx1.14"(29mm)H	
SYF-8816 Directonal LEDs Meets SAE J595 Class 1; Certified E6		
Flash Pattern	: Twenty selectable "strobing" patterns	3W x 6 LEDs
Working Voltage	: DC 12V~24V	Av. Current: 0.7A (12V)
Size	: 4.41"(112mm)Lx1.10"(28mm)Wx0.35"(9mm)H	
SYF-8826 Directonal LEDs Meets SAE J595 Class 1; Certified E6		
Flash Pattern	: Twenty selectable "strobing" patterns	3W x 12 LEDs
Working Voltage	: DC 12V~24V	Av. Current: 1.4A (12V)
Size	: 5.24"(133mm)Lx2.23"(56.8mm)Wx0.47"(12mm)H	
SYF-8826D Directonal LEDs Meets SAE J595 Class 1; Certified E6		
Flash Pattern	: Twenty six selectable "strobing" patterns	3W x 12 LEDs
Working Voltage	: DC 12V~24V	Av. Current: 1.4A (12V)
Size	: 4.45"(113mm)Lx2.23"(56.8mm)Wx0.35"(9mm)H	