## E . Excellent in hydraulic pressure resistance :

The static hydroststic pressure of TAI-PORUXTM HOUSEWRAP is excessive of 200cmH2O. waterspout which can resist rain to seep into from outsi de.

## F . More comfortable to live , To enhance the inhabitant quality :

To lay waterproof and permeable **TAI-PORUXTM HOUSEWRAP** in house can help indoor moisture discharge outward enabling to keep free of dew condensation and getting mildewed, and in result the air quality indoor can be elevated, more comfortable to live for people.

# G. Light weight , Easy to construct :

The advantage of **TAI-PORUXTM HOUSEWRAP** house wrap membrane is light in weight, convenient to carry, and easy to install.





Profile of TAI-PORUXTM HOUSEWRAP Left TPX-S type

Right TPX-W type

# • The basic properties of TAIPORUX<sup>TM</sup> HOUSEWRAP :

Properties	Method	TAI-PORUX™ (TPX-S)	TAI-PORUX™ (TPX-W)
Basic Welght	TAPPI T-41 (oz/yd2)	3.23	1.99
Breaking strength	ASTM D882 Method A (ibs/in) MD/CD	21.3/17.2	35.2/23.5
Tear Strength (trapezoid)	ASTM D-5733 (Ibs) MD/CD	4.8/7.1	20.5/18.3
Elemendorf Tear Resistance	ASTM D-5734 (Ibs) MD/CD	1.2/1.4	19.7/20.6
Air Penetration	Air - Iins (cfm/ft2@75Pa) Gurley Hill (TAPPI T-460) (sec/100cc)	0.031 458	~ 0 750
Water Vapor Transmission	ASTM E-96 Method B (g/m2.24hr) (perms)	576 82.9	837.3 120.5
Water Penetration Resistance	AATCC 127 (cm)	483	Over 200
Weather	JIS L 1415&	Passed	Passed

# **TAI-PORUX**TM HOUSEWRAP

# **UNIQUE TAI-PORUX**TM

New generation product developed and applied to the construction industry

Trading Agent : **UNIQUE PLASTICS CORPORATION** 

P.O. BOX 108-258 TAIPEI, TAIWAN TEL: (886-2) 2741-5391(Rep.) FAX: (886-2) 2776-9998 & 2772-0866 e.mail: uniquepc@ms14.hinet.net http://unique-plastics.net





# • An introduction of TAI-PORUX™ :

TAI-PORUXTM is a product newly developed by UNIQUE PLASTICS CORPORATION. It is made from polyolefin, possessing microporous, waterproof and permeable functions.

The TAI-PORUXTM permeable film is particularly different from those products with tiny aperture made of micro-perforated punch which is easily to let rain getting into. So the TAI-PORUXTM product can competely attain waterproof characteristics.

# The principles of waterproof for TAI-PORUX<sub>TM</sub> :

The size of water-drop 100~3000 micron The size of vapor molecular Approx. 0.00034 micron The size of **TAI-PORUXTM** microporous 0.3~10 micron



The pictures below explain that the moisture vapor can penetrate from micro aperture of TAI-PORUXTM, but the waterdrop can not. That is the principles of waterproof and permeability.



Microporous of TAI-PORUXTM

# What the TAI-PORUX<sub>IM</sub> HOUSEWRAP Stands for ?

TAI-PORUXTM HOUSEWRAP, a new generation and cost saving material, is a composite material made of TAI-PORUXTM film laminated with Polyester non-woven fabric or Polyethylene woven cloth. It has been extensively used for construction material

### The product falls into two categories : Note : (\*) means not available now.

Product	composition	size
TAI-PORUXTM	TAI-PORUXTM/	1.0m x 50m
HOUSEWRAP	PET Non-woven	1.0m x 50m
TAI-PORUXTM	TAI-PORUXTM/	1.5m x 30m
HOUSEWRAP	PE woven cloth	1.0m x 30m
		* 1.5m x 30m
		2 1 20

٦n Λn 0m 2.1m x 20m \* 2.7m x 20m

\* 3.0m x 15m



# • The Characteristics of TAI-PORUX™ HOUSEWRAP :

### A . Good strength , no breakage :

As Tensile strength attains Maximum 35.2lb/inch and tear strength attains Maximum 20.5lb, It is not easy to tear so as to ensure the house wrap's integrity and concretely prove the outstanding functionality of waterproof and permeability

- B. To guard against dew condensation in wall, and to enhance the house life expectancy : It is more easy to creat dew condensation phenomenon in an interior wall because of the temperature distinction in warm and cold weather in the high airtight housing structure, which brings about the corrosion shown on the interior of structure and reduces the life expectancy of use. The waterproof and permeable TAI-PORUXTM HOUSEWRAP enables the moisture in an interior wall to eject outward through microporous and to prevent the dew condensation from occurance.
- C. Remarkable function of waterproof and permeability : The waterproof and permeable TAI-PORUXTM HOUSEWRAP can discharge indoor moisture through micropores. It's permeability can reach Maximum 837g/m2.24hr, and it can completely resist rain to seep through.

## D. Superior to wind protection :

As waterproof and permeable TAI-PORUXTM HOUSEWRAP carries special microporous structure with the high performance of air penetration rate towards to zero, the outside cold air getting into through permeable layer will not seep into the insulation material so as to maintain good optimum temperature effects enabling to make a comfortable living.

	code
٦	TPX - S1050
٦	TPX - S1050
٦	TPX - S1530
٦	TPX - W1030
٦	TPX - S1530
٦	TPX - W2120
٦	TPX - W2720
٦	TPX - W3015

HOUSEWRAP in building structure

