

GSM FIXED CELLULAR TERMINAL

Main Features

- GSM 850/900/1800/1900MHz
- User-friendly installation(Plug & Play)
- DTMF or FSK Caller ID
- LED indicators for signal strength, network and power
- Reverse Polarity signal supporting
- DTMF and pulse dialing
- Emergency Battery back-up
- SMS(optional)
- Payphone Metering pulse supporting(optional)
- GPRS Data transmission(optional)

Technical Specification

Air Interface :

GSM Phase I/GSM Phase II + compatible

GSM Frequency Ranges :

GSM 850/900/1800/1900MHz (Optional)

RF Transmit Power :

2W (900 MHz), 1W (1800/1900 MHz)

RF Sensitivity : <-102 dBm

Electricity Power Supply :

- Input: AC220V/60Hz
- Output :DC 6.5V

Battery Power Supply :

- Type: 1500mAh Ni-MH Batteries x4
- Talk Time: 4h • Standby Time: 24h

LED Indicators :

- Power • Network status • Phone in use • Signal strength

Connectors :

- 2 RJ-11 Interface jack for telephone
- SMA antenna connector • DC power input jack
- Serial port for connecting PC

Antenna : 2dbi Omni Antenna

High-gain antenna and cable as optional

FCT-332



Environment

- Dimension : 183x135x43 mm
- Weight : 1 Kg
- Operating temperature range: -0 °C to +40 °C
- Humidity: 5% to 95% (non-condensing)

Specifications are subject to change without notice

MAXCOMM CO., LTD.

Http://www.maxcomm.com.tw

Email: al.rock@msa.hinet.net

info@maxcomm.com.tw

Tel: 886 2 2966 6648 Fax: 886 2 2969 8296

4F, 283, COUNTY BLVD. SEC.1, BAN CHIAO 220,
TAIPEI HSIEN, TAIWAN R.O.C