

GSM FIXED WIRELESS PHONE MW-17GSM

Stay connected with voice & data cost-effectively!



Technical Specification

- **Air Interface :**
GSM Phase I/GSM Phase II + compatible
GSM with AMR/EFR/FR/HR and CSD
- **GSM Frequency Band:** GSM900/1800MHz or
GSM850/1900MHz
- **RF TX:** 2W (850/900MHz), 1W (1800/1900MHz)
- **Electricity Power Supply :**
Input: AC90~240V/50~60Hz ; Output: DC5.3V/800mA
- **Battery(Optional):** Ni-MH battery, 3.6V/1000mAh
- **Connectors :**
USB port for maintenance or PC(data; optional)
SMA(male) antenna connector
DC power input jack
- **Antenna :** Indoor Antenna; optional outdoor Antenna
- Available casing colour: Black and White

Main Features

- **Operating temperature range :** -10°C to +50°C
- **Humidity :** 5% to 95%
- **Dimensions :** 175mm(L)x165mm(W)x38mm(H)
- **Weight :** <1Kgs

Main Features

- Large 128x64 Dot-Matrix LCD
Yellow-Green or Blue LCD backlight
- Speaker phone for ringing and Hand-Free mode
- Support CID, call forward, call waiting, voice mail,
- 2-Way SMS and 3-Way calling(if network supports)
- STK(if network supports)
- 200-Entry Phone book & 200-Items SMS
- Call history, calendar, schedule, alarm clock, polyphonic ring tone, speed-dialing
- Languages: English(default), Spanish, Arabic and others can be provided as options
- USB1.1 interface(for maintenance and data)
- Internal Ni-MH back-up Battery (optional)
Talk time 3 hrs; Stand-by time 96 hrs
- GPRS Data transmission(optional)
- Available casing colour: Black and White



MAXCOMM CO., LTD.

4F, NO. 283, COUNTY BLVD., SEC. 1, BAN CHIAO,
TAIPEI HSIEN 220, TAIWAN, R.O.C.

WWW.MAXCOMM.COM.TW

TEL: 886 2 2966 6648

FAX: 886 2 2969 8296

E-MAIL: INFO@MAXCOMM.COM.TW