

# CDMA Fixed Wireless Terminal FCT-335CDMA

## Main Feature

- DTMF&FSK Caller ID Display
- Supports Call Forwarding/Waiting/Holding and 3-Way Calling
- Supports 12KHz/16KHz pulse and reverse polarity
- Support G3 analogue fax(optional) and data function(optional)
- LED indicators for signal strength, working status and power
- 2 standard RJ-11 port, one for telephone and the other for analogue fax machine
- USB interface data port
- TNC antenna interface or Panel antenna/
- Yagi antenna(optional)
- 10 groups of emergency call



## Technical Specifications

- CDMA2000 1X, backward IS-95A/B
- CDMA frequency: CDMA450/800/1900MHz
- Frequency band width: TX:824MHz~849MHz, RX:869MHz~894MHz
- Maximum Transmitting Power: 23dBm ~ 30dBm@-104dBm
- Electricity Power Supply: Input: AC100~290V/50Hz; Output: DC12V/0.8A
- Receiving Sensibility: -104dBm (FER ≤ 0.5%)
- External DC Voltage:
- Back-up battery: Ni-MH 7.2V/1500mAH, stand by time: 10 hrs, talk time: 2 hrs
- USB data port
- TNC antenna

- CDMA 450/800/1900MHz
- CDMA WLL residential applications
- Cutting call cost via CDMA wireless network
- USB port for internet surfing

## Environment

- Working temperature: -10°C ~+ 55°C
- Storage temperature: -40°C ~+ 70°C
- Relative Humidity: <95%
- Dimension: 220mmx140mmx40mm
- Weight: 550g

[WWW.MAXCOMM.COM.TW](http://WWW.MAXCOMM.COM.TW)

**MAXCOMM CO., LTD.**

4F, 283, COUNTY BLVD., SEC.1, BAN CHIAO  
TAIPEI HSIEN 220, TAIWAN

TEL : 886 2 2966 6648;

FAX : 886 2 2969 8296

EMAIL : [info@maxcomm.com.tw](mailto:info@maxcomm.com.tw)

[al.rock@msa.hinet.net](mailto:al.rock@msa.hinet.net)