

# CDMA FIXED WIRELESS TELEPHONE MW13CDMA

- CDMA 450/800/1900MHz
- CDMA WLL residential applications
- Cutting call cost via CDMA Wireless Network
- Data port for broadband Internet

## Main Features

- Qualcomm CDMA Module
- User-friendly Operation menu
- With RUIIM Card or without RUIIM
- RUIIM Card locking and Network locking
- 150 entries Phonebook
- SMS storage, 50 inbox; 30 outbox
- Clock shows time while stand by
- Hand-Free feature and Volume control
- Last 10 called numbers record
- Last 10 received call numbers record
- Last 10 missed call numbers record
- Call forwarding feature
- 16 x 2 characters with icon LCD Display
- Optional USB data port
- Back up power Battery

## Environment

- **Operating temperature range** : 0 to +55 degree C
- **Storage temperature range** : -10 to +65 degree C
- **Humidity** : 5% to 95%
- **Dimensions** : 200mm(L)x170mm(W)x55mm(H)
- **Weight** : Appx. 1Kgs

**MAXCOMM CO., LTD.**

[WWW.MAXCOMM.COM.TW](http://WWW.MAXCOMM.COM.TW)

[al.rock@msa.hinet.net](mailto:al.rock@msa.hinet.net), [info@maxcomm.com.tw](mailto:info@maxcomm.com.tw)

Tel: +886 2 2966 6648 Fax: +886 2 2969 8296

4F, 283, COUNTY BLVD. SEC.1, BAN CHIAO,  
TAIPEI HSIEN 220, TAIWAN



## Technical Specification

### Air Interface :

CDMA2000 1X, backward compatible IS-95A

### CDMA Frequency Ranges :

CDMA 450MHz; 800MHz, 1900MHz

### RF Transmit Power :

2W (800 MHz), 1W (1900 MHz)

### RF Sensitivity : < -103 dBm

### Electricity Power Supply :

• Input: AC220V/60Hz • Output : 4.6V, 1000mA

### LCD Display :

• 2-Line LCD Display with status indicator

### Battery Supply :

• Rechargeable Ni-MH Battery

• Capacity: 1300mAh

**Antenna** : Attached 2dbi Omni directional Antenna

**Specifications are subject to change without notice**