

GENERAL FEATURES

- Network:WCDMA/HSDPA /(HSUPA)EDGE/GPRS/GSM
- Working frequency:WCDMA/HSDPA(HSUPA): 850/900/2100 MHz GSM/GPRS/EDGE: Quad-Band 850/900/1800/1900 MHz
- Standard:
- WCDMA/ HSDPA(HSUPA): Compliant to 3GPP R99&R5(&R6 for PHU9) GPRS/EDGE: Compliant to 3GPP R99
- Output power: WCDMA 850:0.25W GSM850/GSM900: 2W DCS1800/PCS1900: 1W
- Antenna: Internal
- Dimensions:
 - 76mmX29mmX12.5mm(including USB cap and antenna)
- 3 color LED indicator for network status
- · Weight: about 40g
- · Lower power consumption
- OS support:WinXP,Win2003,Vista
- Normal operation temperature: -15℃ to +55℃

SPECIFICATIONS FOR DATA TRANSFER

- · Circuit switched data
- U-36:HSDPA support 3.6Mbps downlink

- D-72:HSDPA support 7 2Mbps downlink
- U-72:HSUPA support 7.2Mbps downlink, 2Mbps Uplink
- Dual antenna receiver diversity
- GPRS/EDGE MS Class 10, MCS1–MCS9

INTERFACES

- USB 2.0
- SIM Card

SOFTWARE FEATURES

- SMS
- Phone book
- Plug and play
- 4G memory (optional)









MAXCOMM CO., LTD

4F, No. 283, County Blvd., Sec. 1, Ban Chiao, Taipei Hsien 220, TAIWAN, R.O.C. TEL: +886-2-2966-6648 FAX: +886-2-29698296 E-MAIL: info@maxcomm.com.tw; al.rock@msa.hinet.net

WWW.MAXCOMM.COM.TW