

# EVDO USB MODEM CM100



## Technical Specification

### • Air Interface :

CDMA800MHz: Power class 3, Band class 0

CDMA1900MHz: Power class 2, Band class 1

EVDO Rev. A(IS-856-A)

Downlink: 3.1Mbps; Uplink: 1.8Mbps

CDMA 1x RTT(IS-2000 Rel 0.)

Forward and reverse link speed up to 153.6Kbps(limited by network availability)

### • Standards :

IS-856, IS-856-A(CDMA 1x EVDO Rev. A

IS-866(CDMA 1x EVDO Rev. 0 and A

IS-2000 Rel. 0(CDMA 1x RTT)

IS-707-A Data service

IS-863C OTA Service Provisioning

IS-853-C Wireless IP network

IS-707 AT command

## Main Features

- Phone Book Management: Received calls, Unreceived calls, Dialed calls, Contact numbers.
- SMS Management.
- UIM card needed.
- 2 LED indicators.
- Supports T-Flash card(upto 8GB).
- 512Mbit NAND+ 512Mbit DDR(Available built-in storage: 20MB).
- Supports voice function(virtual keypad).
- Built-in installation software and user manual.
- Built-in worldwide CDMA operators list and settings.
- LAN & WLAN access of high-speed data
- USB port for connecting with printer

## Environment

- Operating temperature : -10°C to 55°C
- Operation Humidity : 10% to 90%

**MAXCOMM CO., LTD.**

4F, NO. 283, COUNTY BLVD., SEC. 1, BAN CHIAO,  
TAIPEI HSIEN 220, TAIWAN, R.O.C.

**WWW.MAXCOMM.COM.TW**

TEL: 886 2 2966 6648

FAX: 886 2 2969 8296

E-mail: [INFO@MAXCOMM.COM.TW](mailto:INFO@MAXCOMM.COM.TW)