

# EVDO WiFi Router WR-35



## Technical Specification

- **Air Interface :**  
EVDO/CDMA2000 1x 450/800/1900MHz
- **EVDO Rev. A:** 3.1Mbps downlink/1.8Mbps uplink
- **AC/DC Power Supply :**  
Input: AC100~240V/50~60Hz, 0.68A  
Output: DC 9V/1.5A  
Car Power Charger: 5V
- **Connectors :**  
4 RJ-45(LAN) port or 3 LAN+1 WAN(optional)  
1 RJ-11(phone) port  
1 DC power input jack
- **Antenna :** Internal WiFi/EVDO/CDMA high gain antenna;  
optional external antenna for EVDO/CDMA available
- **Indicators :** Power,Connect,WiFi,Signal,Network Mode
- **WiFi :** IEEE 802.11b/g/n protocol
- **WPS:** WiFi Protected Setup supportd



## Main Features

- 5 LED indicators: Power,Connect,WiFi,Signal, Network Mode
- Built-in HSUPA modem at a rate of 3.1Mbps downlink, 1.8Mbps uplink
- Supporting Web base Management and plug & play
- Supporting DHCP Server, NAT, Virtual Server, SNTP, Static Routing, DNS Relay, UPnP, DMZ, MAC/URL/ IP filter, VPN passthrough, WiFi 802.11b/g/n
- RJ-11 phone port for analogue phone connection
- RJ-45 ports for 4 users to log on 3G network (not including WiFi users)
- LAN & WLAN access of high-speed data

## Environment

- **Operating temperature :** 0°C to 50°C
- **Operation Humidity :** 10% to 90%
- **Dimensions :** 191mm(L)x118mm(W)x30mm(H)
- **Weight :** <500 g

4F, NO. 283, COUNTY BLVD., SEC. 1, BAN CHIAO,  
TAIPEI HSIEN 220, TAIWAN, R.O.C.

[WWW.MAXCOMM.COM.TW](http://WWW.MAXCOMM.COM.TW)

TEL: 886 2 2966 6648

FAX: 886 2 2969 8296

E-mail: [INFO@MAXCOMM.COM.TW](mailto:INFO@MAXCOMM.COM.TW)