

打頭機 HEADING MACHINE

model 機型	max. length of parts 最大可製外徑(mm)	max. length of parts 最大可製長度(mm)	output/minute 每分鐘生產量 (PC/min)	main slider stroke 主機台衝程(mm)	P.K.O. stroke P.K.O衝程(mm)	die dia 主模尺寸 (mm)	1st punch dia. 第一衝模 外徑(mm)	2nd punch dia. 第二衝模 外徑(mm)	3rd punch dia. 第三衝模 外徑(mm)	motor (HP) 主馬達馬力
WSM1552	5	52	170-190	80	10	34.5x67.5	31	31	19	3
WSM1564	5	64	160-180	92	10	34.5x80.5	31	31	19	3
WSM1576	5	76	120-150	120	10	34.5x100.5	31	31	19	3
WSM20102	6	102	80-100	160	15	48x135.5	38	38	25	7.5
WSM20152	6	152	50-65	220	15	60x200.5	38	38	25	7.5
WSM20200	6	200	40-50	270	15	60x260.5	38	38	25	7.5
WSM20250	6	250	30-40	310	15	60x300.5	38	38	25	7.5
WSM25102	8	102	70-90	160	25	60x140.5	38	38	50	10
WSM25200	8	200	40-50	280	25	80x250.5	38	38	50	15
WSM25250	8	250	30-40	400	25	80x350.5	38	38	50	15

WSM-1552
High-speed Screw Header
(half-closed type)



WSM-20152
(half-closed type)



WSM-1552
High-speed Screw Header
(fully-closed type)



WSM-20152
High-speed Screw Header
(fully-closed type)

