

# 850 S-TYPE Specification

## ENGINE :

4 Cycle Gasoline -- Made in Japan (Oil-Type Air Filter)

Type : GM291 : 8 HP / 2000 rpm Mitsubishi Engine Weight : 26 KG

GM301 : 10HP / 2000 rpm Mitsubishi Engine Weight : 27 KG

Ignition : Electronic

Start Mode :Recoil Starter

Fuel Tank : 6 liter

## The Device:

Gearshift Mode	Direct shifting-gear drive for 2 forward / 2 reverse movement	
Transmission	Belt / Tension wheel drive	
Speed	Forward	High Speed : 3.50
	(km/hr)	Low Speed : 1.84
	Backward	High Speed : 4.86
	(km/hr)	Low Speed : 2.58
Tillage part	Rotary speed of the tillage blade (including the secondary gear-change) (rpm)	1 / 570          2 / 303
		3 / 496          4 / 267
Adjustable Tread	Narrowest : 18cm	
	Widest : 36cm	
Tire Specification	350-5 herringbone design	

Tillage	Depth (cm)	3-25
	Width (cm)	65
Banking up	Ditch Depth (cm)	3-30
	Ditch Width (cm)	18、 24、 30、 36、 45
Dimension ( L x W x H )	145 x 65 x 85 (cm)	
Adjustable Handle	5-section height adjustment	
Net Weight	110kg (including 6-rotary tillage blade , excluding the engine)	