

2 in 1 Transformer Testing System

6265 + 7631

Feature

- One-stop test solution (6265/6266/6267 transformer tester + 7631 Hipot tester)
- The 7631 hipot is the main control instrument, which controls the measurement sequence

6265/6266/6267 Transformer Tester

- Basic accuracy up to 0.1%
- 20 channels
- Max. Test frequency 1MHz

7631 Hipot Tester

- 8 channels
- Support AC output voltage 5000V, DC output voltage 6000V, Insulation Resistance output voltage 1000Vdc
- Arcing detection
- Adjustable ramp time (0.1s-10s)

Applications

Power transformer, electronic transformer



CE

Accessories / Fixtures

- | Standard | Optional |
|------------------------------|---------------------------|
| - Power Cord | - PC Link software |
| - User Manual (CD) | - RS-232 cable |
| - HV Test Cable | - Dual Scan Box (F7721-D) |
| - D-Sub footswitch (F522010) | |
| - Remote Control Cable | |
| - Scan Box (F7721) | |

Specification

6265/6266/6267 Transformer Tester

Test Frequency	200kHz/500kHz/1MHz
Channel	20

Parameters Measurement Ranges and Accuracy	Inductance (L), Impedance (Z), Capacitance (C), Resistance (R), Conductance (G), Susceptance (B), Admittance (Y), Alternating Current Resistance (ACR), Quality Factor (Q), Phase angle (\emptyset), Direct Current Resistance (DCR), Leakage Inductance, Turn Ratio, Balance, Short Circuit
	L, LK 0.1nH-9999.99H
	C 0.00001pF-999.99mF
	Q, D 0.00001-99999
	Z, X, R 0.00001Ω-99.9999MΩ
	Y 0.01nS-99.9999S
	θ -180°+180°
	DCR 0.1mΩ-99.999MΩ
	Turn-Ratio 0.1-99999.9 turns
	Pin-Short 12 pairs, between pin to pin

7631 Hipot Tester

Channel	8
AC Hipot	
Output Voltage	100V-5000V
Voltage Resolution	1V
Voltage Accuracy	±(3% of setting+5V)
Leakage Current	0.001-31mA
Arcing Detection	1-20
DC Hipot	
Output Voltage	10-6000Vdc
Voltage Resolution	1V
Voltage Accuracy	±(3% of setting+5V)
Leakage Current	0.001-11mA
Arcing Detection	1-10
IR	
Output Voltage	10-1000Vdc
Voltage Resolution	1V
Voltage Accuracy	±(3% of setting+5V)
IR Upper Threshold	1-12000MΩ

General

Model Name	6265/6266/6267 Transformer Tester	7631 Hipot Tester
Built-in Storage	128 sets	30 sets
Interface	RS-232, Handler, LAN, USB Host, EXT. I/O	RS-232, Remote, USB Host/Device, EXT. I/O
Power Supply	Voltage 90Vac-125Vac or 190Vac-250Vac	Voltage 90Vac-264Vac
	Frequency 47Hz-63Hz	Frequency 50/60Hz ± 5%
Display	800*480 Color Screen, 7" TFT	480*272, 4.3" TFT LCD
Dimension (W*H*D)	435×145×522mm	435×145×500mm
Weight	9kg	15kg