


TSC 1 SELF-CLINCHING STANDOFFS



Through Threads

Blind Threads

Through - Hole Threads

DIMENSIONS & SPECIFICATIONS																		(MILLIMETERS)					
THREAD SIZE	PART NO.	L LENGTH + .05 / - 0.13														D DIM +0.08 -0.00	H HEX DIM (NOM.)	C COUNTER BORE ±0.13	MIN	MIN			
		3	4	6	8	10	12	14	16	18	20	22	25										
M3x0.5	350																4.2	4.19	4.8	3.2	6.0	1.0	
	350B																5.4	5.38	6.4	3.2	7.0	1.0	
M3.5x0.6	356																5.4	5.38	6.4	4.0	7.0	1.0	
M4x0.7	470																7.2	7.11	7.9	4.8	8.0	1.3	
M5x0.8	580																7.2	7.11	7.9	5.2	8.0	1.3	
S DIM. MIN.			3.2	4.0	5.0	6.5	9.5																
T ± 0.40	NONE			4.0	8.0	11.0																	

DIMENSIONS & SPECIFICATIONS																				(INCH)			
THREAD SIZE	PART NO.	L LENGTH + 0.002 / - 0.005														C DIM +0.003 -0.000	H HEX DIM (NOM.)	D counter. BORE ±0.05	MIN	MIN			
		0.125	0.1875	0.250	0.3125	0.375	0.4375	0.500	0.5625	0.625	0.6875	0.750	0.8125	0.875	0.9375						1.0	1.0625	
#4-40	440																0.166	0.165	0.1875	0.125	0.23	0.040	
	440B																0.213	0.212	0.25	0.125	0.27	0.040	
#6-32	632																0.213	0.212	0.25	0.156	0.27	0.04	
	632B																0.281	0.280	0.3125	0.156	0.31	0.05	
#8-32	832																0.281	0.280	0.3125	0.188	0.31	0.05	
#10-30	1032																0.281	0.280	0.3125	0.203	0.31	0.05	
S DIM. MIN.	FULL THREAD		0.1563	0.1875	0.25	0.375																	
T ± 0.0156	FULL THREAD			0.1875	0.3125	0.4375																	