

SPEED PIN RIVETS

3/16" DIAMETER	PART NUMBER	(L) LENGTH		GRIP RANGE (G)					
		(INCH)	(MM)	NOM		MIN.		MAN.	
				(INCH)	(MM)	(INCH)	(MM)	(INCH)	(MM)
LINER HEAD	TSP4.8L-1	0.281	7.137	0.125	3.175	0.075	1.905	0.175	4.445
	TSP4.8L-2	0.391	9.931	0.219	5.563	0.175	4.445	0.275	6.985
	TSP4.8L-3	0.484	12.294	0.313	7.950	0.275	6.985	0.375	9.525
	TSP4.8L-4	0.578	14.681	0.406	10.312	0.375	9.525	0.475	12.065
	TSP4.8L-5	0.688	17.475	0.531	13.487	0.475	12.065	0.575	14.605
	TSP4.8L-6	0.781	19.837	0.625	15.875	0.575	14.605	0.675	17.145
	TSP4.8L-7	0.875	22.225	0.719	18.263	0.675	17.145	0.775	19.685
	TSP4.8L-8	0.984	24.994	0.813	20.650	0.775	19.685	0.875	22.225
	TSP4.8L-9	1.078	27.381	0.906	23.012	0.875	22.225	0.975	24.765
TAMPER PROOF PIN (TPP)	TSP4.8T-1	0.281	7.137	0.125	3.175	0.075	1.905	0.175	4.445
	TSP4.8T-2	0.391	9.931	0.219	5.563	0.175	4.445	0.275	6.985
	TSP4.8T-3	0.484	12.294	0.313	7.950	0.275	6.985	0.375	9.525
	TSP4.8T-4	0.578	14.681	0.406	10.312	0.375	9.525	0.475	12.065
	TSP4.8T-5	0.281	7.137	0.125	3.175	0.075	1.905	0.175	4.445
	TSP4.8T-6	0.391	9.931	0.219	5.563	0.175	4.445	0.275	6.985
	TSP4.8T-7	0.484	12.294	0.313	7.950	0.275	6.985	0.375	9.525
	TSP4.8T-8	0.578	14.681	0.406	10.312	0.375	9.525	0.475	12.065