

## 介紹 DESCRIPTION

The MEA is non-inductively wound using a metallized polyester film dielectric/electrode with axial leads, flat oval shape and Wrapped in flame-retardant tape and sealed with a moisture resistant epoxy resin at both ends.

MEA 為無感電容，以金屬化聚酯薄膜捲繞，扁橢圓形包裹於麥拉膠帶中，點焊鍍錫軸向引線於兩端，再以環氧樹脂包封兩端。

## 特性 FEATURE

- Self-healing characteristics provide stability.
- moisture resistant.
- Small size、light weight and high capacitance value available.
- 自癒性高、穩定度高
- 防潮性佳
- 體積小、重量輕、高電容值



## 用途 APPLICATION

- Widely used in communication and industrial and auto control system :
- Suitable for charge/discharge, low voltage power and lighting.
- Blocking, by-pass, critical coupling and frequency modulation.
- 廣泛運用於通信設備、工業及自動控制系統：
- 適用於充電/放電、低電壓源及照明。
- 阻斷、旁路、臨界耦合及頻率調制。

## 規格 SPECIFICATIONS

引用標準 Reference Standard	IEC 384-2 grade I ; GB 7334
溫度範圍 Temperature Range	-40°C ~ + 85°C 85°C 至 105°C 之間以1.25%/°C遞減電壓 From 85°C up to 105°C with derating voltage 1.25%/°C.
電容誤差 Capacitance Tolerance	M = ± 20%, K = ± 10%, J = ± 5%
散逸因素 Dissipation Factor(DF)	DF ≤ 1.0% at 20°C ,1KHz
耐電壓 Voltage Proof	1.6 * U <sub>R</sub> (1 minute at 20°C)
絕緣電阻 Insulation Resistance(IR)	C ≤ 0.33μF, IR ≥ 9000MΩ C > 0.33μF, IR * C ≥ 3000MΩ (1 minute at 20°C and RH ≤ 65%)
耐久度 Endurance	1000 hours with 125% of rated voltage at 85°C after the test. 85°C條件下，125%之額定電壓 1000 小時，試驗完成後： ΔC/C ≤ 5%, Δ(DF) ≤ 0.20% (20°C, 1KHz)

尺寸可依需求製作 Size(L x H x T) can be adjusted to meet customers special requirement.