

PORTABLE DRYWALL LIFTER-DW



Electric remote control
With Variable Speed control.



Emergency Stop Button



Manually
Manual available in case of power failure.



Level
Equipped to ensure the proper set up.

1. The distance of two end arms up to 358 cm to take sheets up to 4 foot x 16 foot.
2. **3 in 1, it can be operate in horizontal, vertical and ceiling positioning.**
3. Vertical loading height without ground clearance.
4. Mounted on 5 inches of caster without ground clearance.
5. **Set-Up without tools:** The legs can be release or fold in second without tools.
6. Electric remote control with variable speed switch. The **variable speed control** can be soft start or adjust the micro operating height.
7. **Emergency Stop Button:** Press the button for stop raising or lowering immediately for emergency.
8. Manual operating in case of power failure.
9. Completely portable, lightweight design for you to easy carry
10. Telescoping Mast: Constructed by heat treated, robust aluminum, compact and reliability.
11. **Automatic Overload Breaker:** It equipped to prevent over weight loading.

KSF Drywall Lifter is design by electrical motor, one person can easily operate it. It suitable for position the drywall board, panel, insulation boards and similar sheets.



Specification (Specification changed without notice)

MODEL	DW-340	DW-520
Lifting height	345 cm	520 cm
Wallboard capacity	Up to 4"x16"(122cmx488cm)	
Load capacity	90kg	68kg
Basic height	102 cm	138 cm
Loading Height (Vertical)	0 cm	0 cm
Loading height (Horizontal)	57 cm	92 cm
Machine weight	26 kg	30 kg
Cradle weight	8 kg	8 kg
Dimension	143x37x32 cm	143x37x32 cm
Gross weight	38 kg	41 kg